

Feature



Professional

SE600 engineered to be a medical Electrocardiograph system, complying professional high level standards, using high quality measurement accessories.



Simple

Color 7 inch Full touch screen, for your convenience operation by both touch and short-cut hot keys, enable 12-lead simultaneous sampling and displaying at the same time.



Cost-effective

Super pricing ratio and special distribution policy support available!



Connectivity

Built-in case database management system can store 1000 cases, standard USB export also can review the records, analyse and print the reports by PC through standard PC station software.



Accurate

12 leads simultaneous acquisition, with advanced algorithm for automatic measurements and interpretation, ensure good reading and accurate during different situation.



Reliable

Constructed by sturdy materials case highly resist for critical environmental influence, also reduces electromagnetic interference that disrupt measurements, very suitable for long time monitoring.



Smart

Smart and user-friendly operation system, with the quick start capability and one-button workflow, the lead map help users with lead placement and identify poor connections or missing electrodes easily.



Sino-Hero(Shenzhen)Bio-Medical Electronics Co., LTD.

Tel : + 86-755-26408541 | 26404878 Email: sales@sinoheromed.com Fax: + 86-755-26420566 Web:www.sinoheromed.com

Add: A area, Second Floor, First Building, Tongkangfu Industrial Park, Yingrenshi Community, Shiyao Sub-district, Bao'an District, 518108 Shenzhen, PEOPLE'S REPUBLIC OF CHINA

Version: V4.0

SINOHERO
touching for life

Full Touch Screen

6-CHANNEL Electrocardiograph



 **SE600**



Professional



Accurate



Reliable



Smart



Simple



Cost-effective



Connectivity

Technical Specification

Display Screen

- Display Screen7 Inch Full touch color display
- Resolution800X480 pixels or higher

Size and Weigh

- Product size315mm(L)×210mm(W)×75mm(H)
- Net weight1.7kg

Printing Output

- Recording wayThermal printing system
- Specification of recording paper110 mm(W)×20 m(L) high-speed thermal paper
- Time base selection5 mm/s, 6.25 mm/s, 12.5 mm/s, 25 mm/s, 50 mm/s, 100 mm/s, (paper speed) error: ±5%
- Gain control(sensitivity)2.5, 5,10, 20, 40, 10/5, 20/10mm/mV, accuracy is ±5%
- Standard sensitivity10 mm/mV±0.2 mm/mV

Power Supply

- Voltage100-240 V~
- Frequency50 Hz, 60 Hz
- Input power≤150 VA
- Battery7.4 V, 5000 mAh rechargeable lithium battery

Operation

- Environment temperature5℃~40℃
- Relative humidity25%~95%(no condensation)
- Atmospheric pressure700 hPa~1060 hPa


Transportation and Storage

- Environment temperature-20℃~+55℃
- Relative humidity≤95%
- Atmospheric pressure500 hPa~1060 hPa

Specification

- Time constant≥3.2s
- CMRR>123dB
- FilterAC Filter(AC50/60 Hz), EMG Filter (25 Hz/35 Hz), DFT Filter, Low-pass Filter
- Auto recordRecord setup according to auto record format and mode, automatically change leads, automatically measure and analyze.
- Rhythm recordRecord setup according to rhythm record format and mode, automatically measure and analyze.
- Measurement parametersHR, PR interval, P Duration, QRS Duration, T Duration, QT/QTc interval, P/QRS/T Axis, R(V5) amplitude, S(V1) amplitude, R(V5)+S(V1) amplitude
- Product safety typeClass I type CF defibrillation-proof applied part
- Polarization resistance voltage±950 mV
- Noise level≤12 μVp-p
- ECG signal input sampling frequency32 kHz
- Waveform data processing sampling frequency1 kHz
- Sampling precision24-bit
- The minimum detection signal10 Hz, 20 μV(peak-peak value) deflected sinusoidal signal can be detected
- Pacing detection channelAll leads
- Accuracy of input signal±5%
- Amplitude quantization≤5μV/LSB
- Interchannel time deviation<100 μs
- Input wayFloating and defibrillation protection
- LeadStandard 12 leads
- Patient leakage current<10μA
- Input impedance≥100MΩ(10Hz)

Appearance Characteristics



Thermal Printing System



Interface



Function Button

Accessories

